



📁 Material Handling USA¬

Quote or Site Visit! 222 S. Main St. 5th Floor Salt Lake City, UT 84101

MH-USA





FASTRAK REEL RACKS

Based on the popular FastRak Bulk shelving, these rugged Reel Racks are super strong and highly versatile. Heavy duty uprights are completely welded. Beams attach quickly to uprights using popular "tear drop" design and can be adjusted in 1^{1/2"} increments. Beams also feature a built-in locking clip for added safety. Free standing "Starter Units" include 2 uprights, 3 beams and 3 rods (36" tall units include two rods). Create a row of racks by purchasing "Add-On" units. Customize your rack by purchasing additional rods (1 per level) and brackets (2 brackets are required per level). 1" diameter rod can support up to 350 lbs. per level. Unit capacity is 4,000 lbs.

	Starter Units	Add-On Units		Starter Units	Add-On Units	
W x D	Model Number	Model Number	W x D	Model Number	Model Number	
	3' Hig	h Units		6' High Units		
24″ x 18″	FRS-2418-036	FRT-2418-036	24" x 24"	FRS-2424-072	FRT-2424-072	
36″ x 18″	FRS-3618-036	FRT-3618-036	36″ x 24″	FRS-3624-072	FRT-3624-072	
48″ x 18″	FRS-4818-036	FRT-4818-036	48" x 24"	FRS-4824-072	FRT-4824-072	
	8' Hig	h Units		10' High Units		
24" x 24"	FRS-2424-096	FRT-2424-096	24" x 24"	FRS-2424-120	FRT-2424-120	
36″ x 24″	FRS-3624-096	FRT-3624-096	36" x 24"	FRS-3624-120	FRT-3624-120	
48″ x 24″	FRS-4824-096	FRT-4824-096	48" x 24"	FRS-4824-120	FRT-4824-120	
24″ x 36″	FRS-2436-096	FRT-2436-096	24" x 36"	FRS-2436-120	FRT-2436-120	
36″ x 36″	FRS-3636-096	FRT-3636-096	36" x 36"	FRS-3636-120	FRT-3636-120	
48" x 36"	FRS-4836-096	FRT-4836-096	48" x 36"	FRS-4836-120	FRT-4836-120	



E	ctra Rods	Extra Brackets			
Size	Model Number	Desc.	Model Number		
24" Bar	215-CR01024	Left Bracket	215-CRBL01		
36" Bar	215-CR01036	Right Bracket	215-CRBR01		
48" Bar	215-CR01048				

FASTRAK TIRE STORAGE SHELVING

The FastRak design makes these extra heavy duty units perfect for storing today's larger tires. Recommended for tires that accommodate 16" and larger rims. 48"W, 72"W, and 96"W units accommodate 6, 9, and 12 tires (estimated) per level respectively. All units are 18" deep. Units feature a newly designed upright that can be "knocked down" for easier shipment. Optional deluxe foot plates and concrete wedge anchors are available for added safety.

		Starter Units	Add-On Units		Starter Units	Add-On Units
W x D	# of Levels	Model Number	Model Number	# of Levels	Model Number	Model Number
	8' High Units			10' High Units		
48" x 18"	3	K33S-4818096	K33T-4818096	4	K34S-4818120	K34T-4818120
72″ x 18″	3	K33S-7218096	K33T-7218096	4	K34S-7218120	K34T-7218120
96" x 18"	3	K33S-9618096	K33T-9618096	4	K34S-9618120	K34T-9618120



STOCK RACKS



Vertical Stock Rack - Model# 235-SRV1

High strength tubular steel arms extend 8" from the frame. Pan shelves are spaced 21" apart. The unit base is 36" wide x 24" deep. Unit is 84" high and has a capacity of 3,000 lbs. Unit weight is 80 lbs. Finish: Powder Coated Gray

Horizontal Stock Rack - Model# 235-SRH1

This unit is 84" high x 22" square at bottom and is tapered to $4^{1/2"}$ square at the top. Angled steel arms are spaced every $8^{1/2"}$ and extend 8" from uprights. Capacity per pair of arms is 100 lbs. Unit weight is 60 lbs. Finish: Powder Coated Gray



Two 235-SRH1 shown

Distributed By:



Sales@MaterialHandling-USA.com