

GUARDIAN

STANDARD FEATURES

- Knocked down construction for easy self-assembly or save the labor and order them factory assembled
- Classic III recessed handle designed to accept many styles of locks
- 16 gauge solid door for clean, robust look
- Available with Champagne Common Color bodies or in a single full color
- Lightweight 24 gauge body parts
- Sound dampening pan available to further reduce noise for a slamming door



 **Material Handling USA**
800-326-4403
<https://www.mh-usa.com/>
Sales@MaterialHandling-USA.com



AT A GLANCE

ABOUT PENCO

Penco's nearly 155-year history of providing a full range of storage solutions, achieves an unmatched level of expertise and innovation of products and high level of customer support.

MATERIALS

Steel: All Penco standard lockers are constructed using prime grade steel free from surface imperfection suitable for powder coating. Alternate material: Prime grade steel shall be fabricated using galvanized steel and finished in the same manner. Forged steel coat hooks with balled ends and truss fin head bolts and hex nuts will be zinc coated and supplied for all lockers unless otherwise indicated.

STANDARD LOCKERS

Multi-Point Latch Doors:

- ADA compliant
- will accept combination locks, key locks, padlocks

Hinges:

- two inch high - five knuckle hinges

Solid doors for cleaner/smooth look

Vent slots in the return flange of the door to allow for some ventilation

ADDITIONAL OPTIONS

Doors:

- Continuous hinge option
- 14 gauge door - increases the thickness of the door and helps in situations where lockers are in a slightly harsher environment (Guardian Plus)
- Medallion door - sound pan welded to inside of door, providing reduction in noise when doors are slammed
- SPL Defiant door - combines a 14ga door with a single point latch, continuous hinge, and a reinforcing pan



1 Tier

2 Tier


3 Tier

FINISH

High quality powder coat paint finish applied in strict adherence to paint manufacturer's specifications to provide optimum appearance and performance. Finishes releasing VOCs are not acceptable. Standard coating thickness is 1 mil dry film thickness minimum. Powder Coat Plus option increases thickness to 2 mil minimum. Colors as selected from manufacturer's standard colors.



Defiant II Single Point Latch



Medallion (Option)



Guardian PLUS (Top and Bottom Doors)