



 **Material Handling USA**
800-326-4403
<https://www.mh-usa.com/>
Sales@MaterialHandling-USA.com

VANGUARD

STANDARD FEATURES

- Knocked down construction for easy self-assembly or save the labor and order them factory assembled
- Louvers for ventilation to help avoid awkward smells and moisture build up and still providing privacy inside the locker (other ventilation options available)
- No protruding handles and many lock options available with Penco's Classic III Recessed Pockets
- Available with Champagne Common Color bodies or in a single full color
- Lightweight 24 gauge body parts
- Friction catch/Door pull on 4 tier, 5 tier, and 6 tier lockers
- Extremely rigid and durable with 16 or 18 gauge doors
- Many sizes available in QuickShip with lead times of 2 weeks or less

AT A GLANCE

ABOUT PENCO

Penco's nearly 155-year history of providing a full range of storage solutions, achieves an unmatched level of expertise and innovation of products and high level of customer support.

MATERIALS

Steel: All Penco standard lockers are constructed using prime grade steel free from surface imperfection suitable for powder coating. Alternate material: Prime grade steel shall be fabricated using galvaneal steel and finished in the same manner. Forged steel coat hooks with balled ends and truss fin head bolts and hex nuts will be zinc coated and supplied for all lockers unless otherwise indicated.



1 Tier



2 Tier



3 Tier

STANDARD LOCKERS

Multi-Point Latch Doors:

- ADA compliant
- will accept combination locks, key locks, padlocks

Box locker Doors:

- will accept combination locks, key locks, padlocks

Hinges:

- two inch high - five knuckle hinges
- continuous hinge option available



4 Tier



5 Tier



6 Tier

FINISH

High quality powder coat paint finish applied in strict adherence to paint manufacturer's specifications to provide optimum appearance and performance. Finishes releasing VOCs are not acceptable. Standard coating thickness is 1 mil dry film thickness minimum. Powder Coat Plus option increases thickness to 2 mil minimum. Colors as selected from manufacturer's standard colors.

